

OPTIMAL-LED ‚Produkt Up-Date‘



720Lumen
Modul



1000Lumen
Modul



1300Lumen
Modul

Bestellnummer Order code	AOL 800-27 (2700K) AOL 800-30 (3000K)	AOL 1000-27 (2700K) AOL 1000-30 (3000K)	AOL 1300-27 (2700K) AOL 1300-30 (3000K)
Lumen @ mA	720 Lumen @ 700mA	1000 Lumen @ 1000mA	1300 Lumen @ 1000mA
Wattage	8W	13W	18W
Lichtfarbe Colour temperature	2700/ 3000K	2700/ 3000K	2700/ 3000K
Passende Netzteile Suitable driver	TLA 700-18 TLA 700-18-D (DIM)	TLA 700-18-D (DIM)	TLA 700-18-D (DIM)

Diese neue Ausführungen sind erhältlich ab 02/ 2013 | This new versions are available from 02/ 2013

OPTIMAL-LED können durch das einfache Adaptersystem mit hoch entblendeten Reflektoren wahlweise im Abstrahlwinkel 20°, 40° oder 60° bestückt werden.

Bitte bestellen Sie diese jeweils separat (siehe unten). Neben den standardmäßigen LEDs mit 2700/ 3000K und CRI >80 sind projekt-spezifisch auch CRI 95 Ausführungen und Lichtfarben von 4000K lieferbar.

Thanks to the easy-to-use adapter system, OPTIMAL-LED can be used with anti-glare reflectors, and can have light distribution angles of 20°, 40° or 60°. Please order separately (see below).

In addition to standard LEDs with 2700/ 3000K and a CRI >80, we can also supply versions with 4000 K and CRI's up to 95.

Passende Reflektoren Suitable reflectors



20°

ZOR K2S



40°

ZOR K4S



60°

ZOR K6S

